

## TL – Tank L-Shape - Steel or Aluminum

Tanks are heavy duty, and offer auxiliary supply for water, diesel, oil and/or biofuels. Tanks can be mounted on or in truck box, flatbed and trailer. **It is the user's responsibility to comply with local, state and federal requirements pertaining to safe transportation, loading and discharging of tank contents. These tanks are not intended to be used for gasoline or cannot be used to transfer gasoline to another vehicle. ATB Secure & Trusted Design.**

### Description

- An engineered steel or aluminum construction
- Fully seam welded on all seams and corners
- Built-in baffles to reduce sloshing
- 2" female pipe tread couplings - inside reinforced
- 1-1/2 top fitting for sensor and 3/8" bottom drain
- Designed to work with 20" to 28" cross boxes or chest boxes
- Pressure tested for leaks
- Double Coated - Zinc epoxy primer & MR powder baked topcoat
- Mounting bracket tabs to secure tank
- Tanks to be used with diesel fuel only – Use only vented filler cap
- Mounting kit included - M3700 Series




TL41 & TL51



TFC21-AU-A



TL42 & TL52 Tank



**Tanks should be mounted to ATB mounting installation guideline. Failure to properly mount tank will void warranty.**

**Note:** \*Tanks are available in multiple colors: Black (B) and White (W) Finish

No.	Model Number	Material	Height (in.)	Depth (in.)	Width (in.)	Height A (in.)	Height B (in.)	Depth C (in.)	Depth D (in.)	Pickup Box	Mounting Kit	Capacity (Gallons)	Weight (lb.)
1.	A-TL51-203148S-*2	.125 Alum	20	31	48	10	10	11	20	Any	M3705	78	92
2.	A-TL51-243148S-*2	.125 Alum	24	31	48	14	10	11	20	Any	M3705	86	97
3.	A-TL51-243154D-*2	.125 Alum	24	31	54	14	10	11	20	8'	M3705	98	108
4.	A-TL51-243554D-*2	.125 Alum	24	35	54	14	10	11	24	8'	M3705	110	115
5.	A-TL52-243158D-*2	.125 Alum	24	31	58-49	14	10	11	20	6'-6-1/2-8'	M3705	94	108
6.	A-TL52-243558D-*2	.125 Alum	24	35	58-49	14	10	11	24	6-1/2-8'	M3705	102	112
7.	A-TL52-243958D-*2	.125 Alum	24	39	58-49	14	10	11	28	6-1/2-8'	M3705	110	120
8.	A-TL52-263758D-*2	.125 Alum	26	37	58-49	16	8	13	24	6-1/2-8'	M3705	102	117
9.	A-TL52-264158D-*2	.125 Alum	26	41	58-49	16	8	13	28	6-1/2-8'	M3705	110	125
10.	S-TL41-203148S-*2	14g Steel	20	31	48	10	10	11	20	Any	M3705	78	164
11.	S-TL41-243148S-*2	14g Steel	24	31	48	14	10	11	20	Any	M3705	86	174
12.	S-TL41-243154D-*2	14g Steel	24	31	54	14	10	11	20	8'	M3705	98	190
13.	S-TL41-243554D-*2	14g Steel	24	35	54	14	10	11	24	8'	M3705	110	202
14.	S-TL42-243158D-*2	14g Steel	24	31	58-49	14	10	11	20	6'-6-1/2-8'	M3705	94	190
15.	S-TL42-243558D-*2	14g Steel	24	35	58-49	14	10	11	24	6-1/2-8'	M3705	102	200
16.	S-TL42-243958D-*2	14g Steel	24	39	58-49	14	10	11	28	6-1/2-8'	M3705	110	210
17.	S-TL42-263758D-*2	14g Steel	26	37	58-49	16	8	13	24	6-1/2-8'	M3705	102	206
18.	S-TL42-264158D-*2	14g Steel	26	41	58-49	16	8	13	28	6-1/2-8'	M3705	110	218

**Note:** Tanks are available in different configuration and custom sizes; call the factory for different sizes and options.